

Saint Maxime

Tuft gauge	1/10 cut pile		ISO 2424
Pilecomposition	100% PA		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1000 gr/m ²		ISO 8543
Total weight	Felt : 2000 gr/m ²	± 15%	ISO 8543
Pile height	10 mm	± 2 mm	ISO 1766
Total Height	Felt : 13 mm		ISO 1765
Number of knots	158000 /m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1		EN 13501-1
GUT Nr.	1567EF44		www.pro-dis.info

Floorsymbols



Certificates



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-003FS155
 Reaction to fire:
 Cfl-s1
 1688
 Slip resistance: DS
 Felt
 Resilient floor
 covering to be
 used within a
 building



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-003FS155-UK
 Reaction to fire:
 Cfl-s1
 1688
 Slip resistance: DS
 Felt
 Resilient floor
 covering to be
 used within a
 building



Intenza
 the ultimate in soft carpets

