

Ancona

Tuft gauge	1/8 cut pile		ISO 2424
Pilecomposition	100% PP		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1800 gr/m ²		ISO 8543
Total weight	Felt : 2650 gr/m ²	± 15%	ISO 8543
Pile height	15.5 mm	± 2 mm	ISO 1766
Total Height	Felt : 18.5 mm		ISO 1765
Number of knots	140.620 /m ²	-7.5% .+10%	ISO 1763
Fire Classification	Efl		EN 13501-1
Use Area	Heavy domestic use (23)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-001FA214
 Reaction to fire:
 Efl
 Slip resistance: DS
 Felt
 Resilient floor
 covering to be
 used within a
 building



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-001FA214-UK
 Reaction to fire:
 Efl
 Slip resistance: DS
 Felt
 Resilient floor
 covering to be
 used within a
 building



Intenza
 the ultimate in soft carpets

