

Caruso

Tuft gauge	1/8 cut pile	ISO 2424
Pilecomposition	100% PES	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	Felt	ISO 2424
Width	400 cm, 500 cm ± 1%	EN 984
Pile Density	0.152 gr/cm ³	ISO 8543
Pile Weight	1550 gr/m ²	ISO 8543
Total weight	Felt : 2450 gr/m ² ± 15%	ISO 8543
Pile height	14 mm ± 2 mm	ISO 1766
Total Height	Felt : 17 mm	ISO 1765
Number of knots	121.920 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Transversal resistance	Ω	ISO 10965
Use Area	Heavy project use (33)	EN 1307
GUT Nr.	2A0E3C2B	www.pro-dis.info
Thermal resistance	ca. 0,14 (1,4 TOG) M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC5	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates

<p>2017</p> <p>Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FC191 Reaction to fire: Cfl-s1 1658 Slip resistance: DS Resilient floor covering to be used within a building</p>	<p>2017</p> <p>Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025FC191-UK Reaction to fire: Cfl-s1 1658 Slip resistance: DS Resilient floor covering to be used within a building</p>
--	---

