







Goodwood

| | | | |
|----------------------------|-------------------------------|--------|------------|
| Tuft gauge | 1/8 cut pile | | ISO 2424 |
| Pilecomposition | 100% PP | | ISO 2424 |
| Primary Backing | Woven | | ISO 2424 |
| Secondary backing | Felt | | ISO 2424 |
| Width | 400 cm, 500 cm | ± 1% | EN 984 |
| Pile Weight | 720 gr/m ² | | ISO 8543 |
| Total weight | Felt : 1720 gr/m ² | ± 15% | ISO 8543 |
| Pile height | 8 mm | ± 2 mm | ISO 1766 |
| Total Height | Felt : 11 mm | | ISO 1765 |
| Fire Classification | Efl | | EN 13501-1 |
| Use Area | Medium domestic use (22) | | EN 1307 |
| Light fastness | ≥ 5 | | 105-B02 |
| Wearebility | ≥ 4 | | 105-X12 |
| Water fastness | ≥ 4 | | 105-E01 |

Floorsymbols



Certificates

| | | | | | |
|---|--|---|---|---|--|
|  2023 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FG026 Reaction to fire: Efl Slip resistance: DS Resilient floor covering to be used within a building |  2023 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-001FG026-UK Reaction to fire: Efl Slip resistance: DS Resilient floor covering to be used within a building |  www.blauer-engel.de/uz128 |  |  |  |
|---|--|---|---|---|--|