

## Infinity

<b>Tuft gauge</b>	1/10 cut pile		ISO 2424
<b>Pilecomposition</b>	100% PES		ISO 2424
<b>Primary Backing</b>	Woven		ISO 2424
<b>Secondary backing</b>	Felt		ISO 2424
<b>Width</b>	400 cm, 500 cm	± 1%	EN 984
<b>Pile Weight</b>	2350 gr/m <sup>2</sup>		ISO 8543
<b>Total weight</b>	Felt : 3260 gr/m <sup>2</sup>	± 15%	ISO 8543
<b>Pile height</b>	14 mm	± 2 mm	ISO 1766
<b>Total Height</b>	Felt : 17 mm		ISO 1765
<b>Number of knots</b>	158000 /m <sup>2</sup>	-7.5% .+10%	ISO 1763
<b>Fire Classification</b>	Cfl-S1		EN 13501-1
<b>Use Area</b>	Heavy domestic use (23)		EN 1307
<b>GUT Nr.</b>	CAFB223E		www.pro-dis.info
<b>Light fastness</b>	≥ 5		105-B02
<b>Wearebility</b>	≥ 4		105-X12
<b>Water fastness</b>	≥ 4		105-E01

## Floorsymbols



## Certificates

 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025F1032 Reaction to fire: Cfl-s1 1658 Slip resistance: DS Felt Resilient floor covering to be used within a building	 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-025F1032-UK Reaction to fire: Cfl-s1 1658 Slip resistance: DS Felt Resilient floor covering to be used within a building	 www.blauer-engel.de/uz128	 DAS UMWELTZEICHEN	 the ultimate in soft carpets	 INDOOR AIR COMFORT	 A+ A B C
---	--	-------------------------------	-----------------------	----------------------------------	------------------------	--------------