

Metro

Tuft gauge	1/8 loop pile	ISO 2424
Pilecomposition	100% PA	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	AB	ISO 2424
Width	400 cm ± 1%	EN 984
Pile Density	0,186 gr/cm ³	ISO 8543
Pile Weight	1080 gr/m ²	ISO 8543
Total weight	AB : 2100 gr/m ² ± 15%	ISO 8543
Pile height	4,1 mm ± 2 mm	ISO 1766
Total Height	AB : 6,7 mm	ISO 1765
Number of knots	108120 /m ² -7.5% .+10%	ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Transversal resistance	3,6*10 ⁹ g ³ ,6*10 ⁹ Ω	ISO 10965
Use Area	Heavy project use (33)	EN 1307
GUT Nr.	24779	www.pro-dis.info
Evaluated sound absorptions grade	0,15 αW	
Sound Insulation	ca. 23 dB	ISO 10140
Thermal resistance	ca. 0.08 (0.8 TOG) M ² KW	ISO 8302
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01
Electrostatic charging	<2 kV	ISO 6356
Luxury class	LC3	EN 1307
Pictures	www.condorcontract.com	

Floorsymbols



Certificates



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-020AM116
 Reaction to fire:
 Cf-s1
 I658
 Slip resistance: DS
 Resilient floor
 covering to be
 used within a
 building



Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP: C-020AM116-UK
 Reaction to fire:
 Cf-s1
 I658
 Slip resistance: DS
 Resilient floor
 covering to be
 used within a
 building

