

Monarch Special

Tuft gauge	1/10 cut pile	ISO 2424
Pilecomposition	100% PA SDN	ISO 2424
Primary Backing	Woven	ISO 2424
Secondary backing	AB, Felt	ISO 2424
Width	400 cm ± 1%	EN 984
Pile Weight	1550 gr/m ²	ISO 8543
Total weight	AB : 2450 gr/m ² Felt : 2550 gr/m ²	± 15% ISO 8543
Pile height	10 mm ± 2 mm	ISO 1766
Total Height	AB : 12 mm Felt : 13 mm	ISO 1765
Number of knots	221200/m ²	-7.5% .+10% ISO 1763
Fire Classification	Cfl-S1	EN 13501-1
Use Area	Heavy domestic use (23)	EN 1307
Light fastness	≥ 5	105-B02
Wearebility	≥ 4	105-X12
Water fastness	≥ 4	105-E01

Floorsymbols



Certificates

CE
2023
Condor Carpets
Euroweg 3
8061 SB Hasselt
EN1307
DOP C-022AM262
Reaction to fire: EI1
Slip resistance: DS
AB
Resilient floor covering to be used within a building

CE
2023
Condor Carpets
Euroweg 3
8061 SB Hasselt
EN1307
DOP C-022FM262
Reaction to fire: EI1
Slip resistance: DS
Felt
Resilient floor covering to be used within a building




