

Radisson

Tuft gauge	1/10 cut pile		ISO 2424
Pilecomposition	100% PA66		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	2190 gr/m ²		ISO 8543
Total weight	Felt : 3000 gr/m ²	± 15%	ISO 8543
Pile height	12 mm	± 2 mm	ISO 1766
Total Height	Felt : 15 mm		ISO 1765
Number of knots	248.220 /m ²	-7.5% .+10%	ISO 1763
Fire Classification	Bfl-S1		EN 13501-1
Use Area	Heavy domestic use (23)		EN 1307
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates

 2017 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-023FRI32 Reaction to fire: Bfl-s1 Slip resistance: DS Felt Resilient floor covering to be used within a building	 2017 Condor Carpets Euroweg 3 8061 SB Hasselt EN1307 DOP: C-023FRI32-UK Reaction to fire: Bfl-s1 Slip resistance: DS Felt Resilient floor covering to be used within a building	 www.blauer-engel.de/uz128			
--	---	---	---	---	--